


ALTA

MODEL NYS 600 SS
600# ANSI STAINLESS STEEL
SCREWED / SOCKET WELD
"Y" STRAINER

DRAWING A113

DESCRIPTION	MATERIAL
BODY	ASTM A-351 GR. CF8M
CAP	ASTM A-351 GR. CF8M
GASKET	SPIRAL WOUND SS
SCREEN	304 SS 1/32 PERF

TEMPERATURE		WORKING PRESSURE	
C	F	kPa	P.S.I.
-29 to 38	-20 to 100	9930	1440
95	200	8550	1240
150	300	7720	1120
200	400	7100	1030

ALL STRAINERS ARE INDIVIDUALLY HYDROSTATICALLY TESTED TO ANSI B16.5

SIZE		DIMENSIONS						NET WEIGHT	
		A		B		C			
mm	in.	mm	in.	mm	in.	mm	in.	Kg.	Lbs.
40	1 1/2	142	5 9/16	112	4 3/8	20	3/4	3.6	8
50	2	177	6 15/16	143	5 5/8	25	1	6.8	15

FEATURES

BODY HAS A MACHINED SEAT TO HOLD SCREEN SECURELY.

CAP HAS A MACHINED SCREEN HOLDER TO ALIGN SCREEN DURING INSTALLATION AND TO RETAIN SEDIMENT WHEN CAP IS REMOVED.

BODY IS MACHINED TO HOLD CAP GASKET IN A BLOW-OUT PROOF DESIGN.